

TRANS DECOSHIELD

Product Description A water based satin 100% acrylic paint specially formulated for interior wall and ceiling surfaces which demand a hard wearing premium quality finish. This product is easy to apply and provides a scrubbable finish.

Recommended Use For use on suitably prepared timber, brick, cement, stone, plasterboard and previously painted surfaces. Ideal for domestic kitchens, bathrooms, laundries, passageways and other high usage living area.

Physical Data	Colour	Available On Request
	Resin Type	Acrylic
	Gloss Level	Satin
	Recommended Film Thickness per Coat	62 microns (wet) 22 microns (dry)
	Theoretical Coverage	Approximately 16.00 sq.m/ltr But this depends upon surface texture and porosity of the surface.
	Packaging	5 litres; 20 litres
	Number of Component	1
	Durability	Interior and exterior
	Flash Point	Non Flammable

Surface Preparation Remove grease, dust and dirt by washing down with a liquid detergent and warm water followed by a rinse with clean water. Allow to dry. All loose, peeling and flaking material must be removed. Sand the surface smooth and remove all dust. Sand glossy painted surfaces until all gloss is removed. Fill holes and cracks with a spackling compound and sand lightly to an even finish.

After identifying the presence of mould, mildew or fungi, it is necessary to remove the growth then sterilise the surface before repainting.

Unpainted Brick, Cement, Stone, Fibre Cement, etc.

No undercoat or sealer required. Ensure that new cement or concrete work is fully cured before applying Trans Decoshield.

Application Data	Application Methods	
	Apply By	Brush, Roller or Spray
	Apply Over	Prepared surfaces
	Clean Up	Wash brushes, rollers and spray equipment with water.
	Thinner	No thinning required, but if necessary thin sparingly with water.
	Cleaner	Brushes, rollers and spray equipment should be cleaned by water.
	Washability	Excellent
	Drying Time	
	Touch Dry	20 minutes (longer under cold or adverse drying conditions)
	Recoat	2 - 3 hours

TRANS DECOSHIELD

CAUTION:

- Provide adequate ventilation during use.
- Do not use below 10°C or when humidity is very high. Avoid painting in temperatures greater than 30°C as a very hot surface will make brushing difficult.
- Avoid exposure to excessive steam and condensation for 48 hours after application of final coat.
- Leave seven days after application of final coat before washing or scrubbing.
- When subject to steam or condensation, all waterbased paints may develop a stain, which can be removed with a damp cloth. For heavy exposure areas use turps based enamels.

Instruction

- Stir content thoroughly with a flat stirrer before and during use.
- Apply two coats by brush, roller or spray equipment.

Disclaimer

The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.
